

CV-221C/P1201 Series

21.5" FHD 16:9 Slim Bezel Panel PC with Intel® Atom® x6211E Dual-Core Embedded Computer, Projected Capacitive Touch, and AG Coating



Slim • Modular • Durable

CV-200/P1000 Series — Modernized Industrial Panel PCs

Overview

[CONTACT](#)

The CV-200 / P1201 series is an entry-level slim-bezel modular industrial panel PC, powered by Intel® Elkhart Lake Atom® processors for stable, reliable computing performance. In addition to a rich set of native I/O interfaces, including GbE LAN, USB 3.2, COM, and DIO, it supports Mini PCIe and M.2 Key E 2230 expansion slots, and can be further extended with Cincoze CFM modules for PoE, IGN, and other functions. The series supports Full HD resolution and is available in sizes from 10" to 21.5". Combined with industrial-grade rugged design, it is ideal for machine HMIs, production process visualization, and a wide range of industrial applications.

Key Features


- 21.5" Full HD LCD (1920 x 1080) with 16:9 Aspect Ratio
- Projected Capacitive Touch with Anti-Glare Coating.
- Wide Viewing Angle of 178°/178°
- Intel® Elkhart Lake Atom® x6425E/x6211E Processor
- Supports Triple Independent Display
- 1x M.2 Key E Type 2230 Socket for Wireless Module
- Designed with Rugged Aluminum Die-casting Front Bezel
- Front Panel IP66 Compliant

Certifications



Next-gen Performance

The CV-200/P1201 supports up to an Intel® Atom® x6425E (Elkhart Lake) 4-core processor, with 1.7 times the single-thread performance, 1.5 times the multi-thread performance, and double the graphics performance of the previous-generation Apollo Lake processor. Up to 32 GB of 3200 MHz DDR4 is supported.





Patented CDS Technology

Convertible Display System (CDS), the patented technology that connects the CV-200 display module to the P1201 embedded computer, has the advantages of easy maintenance in the field and easy future upgrades because the screen size can be changed and performance can be improved by only replacing a single part, rather than the whole system, saving on upgrade costs.

Ultra-Slim Bezel

With an ultra-slim bezel of ≤ 3 mm (varies by display size), the CV-200 minimizes physical constraints for compact installations. It's ideal for space-limited enclosures and applications requiring efficient integration with a streamlined appearance.



Reliable Touch Performance

All models support P-Cap touch, anti-glare (AG) coating, and wet tracking technology, ensuring stable operation and clear visibility even in humid environments or under bright indoor lighting.

Robust, Safe, Reliable

The CV-200/P1201 series has industrial-grade protections, including wide operating temperature, wide-range DC power input (9 to 48 VDC), and IP66 front panel dust and water resistance, to face harsh and dangerous use environments such as on-site HMI and production process visualization. The CV-200/P1201 (19"-24" only) has separately passed product safety standards (UL certification) for information and communication technology and audio-visual equipment in the United States, an assurance of product safety.



CV-221C Series Specifications

Model Name	CV-221C
Display	
LCD Size	• 21.5" (16:9)
Max. Resolution	• 1920x1080
Brightness (cd/m2)	• 300
Contrast Ratio	• 5000 : 1
LCD Color	• 16.7M
Pixel Pitch (mm)	• 0.24825 (H) x 0.24825 (V)
Viewing Angle (H-V)	• 178 / 178
Backlight LED Life Time	• 50,000 hrs (LED Backlight)
Touch Screen	
Touch Type	• Projected Capacitive
Anti-Glare	• V
Wet Touch Tracking	• V
Physical	
Dimension (W x D x H)	• 522.4 x 318.3 x 63.4 mm
Weight Information	• 5.28 kg
Mechanical Construction	• Die-Casting Flat Surface
Power	
Power Consumption	• 24.8 W (Max.)
Environment	
Front Panel Protection	• IP 66 Compliant
Operating Temperature	• 0°C - 60°C (32°F to 140°F) - With Industrial Grade peripherals; Ambient with air flow
Storage Temperature	• -20°C - 60°C (-4°F to 140°F)
Relative Humidity	• 90% RH @ 40°C (non-condensing)
EMC	• CE, UKCA, FCC, ICES-003 Class A
EMI	• CISPR 32 Conducted & Radiated: Class A • EN/BS EN 55032 Conducted & Radiated: Class A • EN/BS EN 50121-3-2 Conducted & Radiated: Class A • EN/BS EN IEC 61000-3-2 Harmonic current emissions: Class A • EN/BS EN 61000-3-3 Voltage fluctuations & flicker • FCC 47 CFR Part 15B, ICES-003 Conducted & Radiated: Class A
EMS	• EN/IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV • EN/IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 20 V/m • EN/IEC 61000-4-4 EFT: AC Power: 2 kV; DC Power: 1 kV; Signal: 2 kV • EN/IEC 61000-4-5 Surges: AC Power: 2 kV; Signal: 1 kV • EN/IEC 61000-4-6 CS: 10V (**Compliant with the standard when utilizing shielded cable.) • EN/IEC 61000-4-8 PFMF: 50/60 Hz, 30A/m • EN/IEC 61000-4-11 (50/60 Hz): Voltage dips duration up to 25/30 cycles; interruptions up to 250/300 cycles.
Industrial Environment	• EMC: - EN/BS/IEC 61000-6-4: 2019 Class A - EN/BS/IEC 61000-6-2: 2019

Railway	• EMC: EN 50155: 2021 Clause 4.4.6, 13.4.9 (w/ M1101 only) - EN 50121-1 : 2017 - EN 50121-3-2: 2016 + A1: 2019
---------	--

P1201 Specifications


Model Name	P1201
System	
Processor	- Intel® Atom® x6425E Processor (1.5M Cache, up to 3.00 GHz, 12W) - Intel® Atom® x6211E Processor (1.5M Cache, up to 3.00 GHz, 6W)
Memory	1x DDR4 SO-DIMM Socket - Supports DDR4 3200MHz Memory Up to 32GB (un-buffered and non-ECC)
BIOS	AMI BIOS
Graphics	
Graphics Engine	Integrated Intel® UHD Graphics
Maximum Display Output	Supports Triple Independent Display
CDS	1x CDS Connector (1920 x 1080 @60Hz)
DP	1x DisplayPort Connector (4096 x 2304 @ 60Hz,According to CPU Specifications) * Verified maximum resolution: 3840 x 2160 @60Hz
VGA	1x VGA Connector (1920 x 1200 @60Hz)
Audio	
Audio Codec	Realtek® ALC888, High Definition Audio
Line-out	1x Line-out, Phone Jack 3.5mm
Mic-in	1x Mic-in, Phone Jack 3.5mm
I/O	
LAN	2x 1GbE LAN, RJ45 - GbE1: Intel® I210 - GbE2: Intel® I210
COM	3x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9
USB	3x 10Gbps USB 3.2 Gen2, Type A 1x 480Mbps USB 2.0, Type A
DIO	8x Isolated DIO (4x DI/4x DO), 10-Pin Terminal Block
Storage	
SSD/HDD	1x 2.5" Front Accessible SATA HDD/SSD Drive Bay (SATA3.0)
mSATA	1x mSATA Socket (SATA 3.0, shared by Mini-PCle socket)
Expansion	
Mini PCI Express	1x Full-size Mini-PCle Socket
SIM Socket	1x SIM Socket
M.2	1x M.2 Key E Type 2230 Socket, Support Wireless Module
CFM (Control Function Module) Interface	1x CFM IGN Interface for optional CFM-IGN Module Expansion 1x CFM PoE Interface for optional CFM-PoE Module Expansion
CDS (Convertible Display System) Interface	1x CDS Interface for Convertible Display Module
Other Function	
Clear CMOS Switch	1x Clear CMOS Switch
Reset Button	1x Reset Button

Watchdog Timer	• Software Programmable Supports 256 Levels System Reset
OSD Button	• LCD On/Off, Brightness Up, Brightness Down
Internal Speaker	• AMP 2W + 2W
Status LED Indicator	• Power LED, HDD LED, Temperature LED
Power	
Power Button	• 1x ATX Power On/Off Button
Power Mode Switch	• 1x AT/ATX Mode Switch
Power Input	• 9 - 48VDC, 3-pin Terminal Block
Remote Power On/Off	• 1x Remote Power On/Off, 2-pin Terminal Block
Remote Power LED	• 1x Remote Power LED, 2-pin Terminal Block
Operating System	
Windows	• Windows® 10
Linux	• Supports by project
Physical	
Dimension (W x D x H)	• 204.5 x 149 x 41.5 mm
Weight Information	• 1.54 kg
Mechanical Construction	• Extruded Aluminum with Heavy Duty Metal
Mounting	• Wall / VESA / CDS / DIN Rail
Physical Design	• Fanless Design • Jumper-less Design
Reliability & Protection	
Reverse Power Input Protection	• Yes
Over Voltage Protection	• Protection Range: 51~58V • Protection Type: shut down operating voltage, re-power on at the preset level to recover
Over Current Protection	• 15A
CMOS Battery Backup	• SuperCap Integrated for CMOS Battery Maintenance-free Operation
MTBF	• 283,091 Hours - Database: Telcordia SR-332 Issue3, Method 1, Case 3
Environment	
Operating Temperature	• -40°C to 70°C * PassMark BurnInTest: 100% CPU, 2D/3D Graphics (without thermal throttling) * With extended temperature peripherals; Ambient with air flow * According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14
Storage Temperature	• -40°C to 85°C
Relative Humidity	• 95%RH @ 70°C (non-Condensing)
Shock	• Operating, 50 Grms (w/ SSD, according to IEC60068-2-27)
Vibration	• Operating, 5 Grms, 5-500 Hz, 3 Axes (w/ SSD, according to IEC60068-2-64) • Operating, 1 Grms, 10-500 Hz, 3 Axes (w/ SSD, according to IEC60068-2-6)
EMC	• CE, UKCA, FCC, ICES-003 Class A • EN IEC 61000-6-4, EN IEC 61000-6-2(24VDC Input Only)


EMI	• CISPR 32 Conducted & Radiated: Class A • EN/BS EN 55032 Conducted & Radiated: Class A • EN/BS EN IEC 61000-3-2 Harmonic current emissions: Class A • EN/BS EN61000-3-3 Voltage fluctuations & flicker • FCC 47 CFR Part 15B, ICES-003 Conducted & Radiated: Class A
EMS	• EN/IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV • EN/IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 10 V/m • EN/IEC 61000-4-4 EFT: AC Power: 2 kV; DC Power: 1 kV; Signal: 1 kV • EN/IEC 61000-4-5 Surges: AC Power: 2 kV; Signal: 1 kV • EN/IEC 61000-4-6 CS: 10V • EN/IEC 61000-4-8 PFMF: 50 Hz, 30A/m • EN/IEC 61000-4-11 Voltage Dips & Voltage Interruptions: 1 cycles at 60 Hz
Safety	• UL, cUL, CB, IEC/EN 62368-1

CV-221C/P1201 External Layout


Front I/O




Rear I/O




Left I/O



Right I/O



CV-221C/P1201 Dimensions



Ordering Information

Available Models

Model No.	Description
CV-221C-R10/P1201-X6425E-R11	21.5" FHD 16:9 Slim Bezel Panel PC with Intel® Atom® x6425E Quad-Core Embedded Computer, Projected Capacitive Touch, and AG Coating
CV-221C-R10/P1201-X6211E-R11	21.5" FHD 16:9 Slim Bezel Panel PC with Intel® Atom® x6211E Dual-Core Embedded Computer, Projected Capacitive Touch, and AG Coating

Model Configuration

	CV-221C	P1201-X6425E	P1201-X6211E
CV-221C/P1201-X6425E	V	V	--
CV-221C/P1201-X6211E	V	--	V

V : Compatible

Package Checklist

• CV-221C/P1201 Series Panel PC x 1	• Power Terminal Block Connector (Female) x 1
• Thermal Pad (for CPU Thermal Block) x 1	• Screw Pack x 1
• DIO Terminal Block Connector (Female) x 1	• Remote Power On/Off Terminal Block Connector x 1
• Panel Mounting Kit x 14	

Optional Modules and Accessories

Model No.	Description
CFM-PoE02	CFM Module with PoE Control Function, Individual Port 25.5W
CFM-IGN101	CFM Module with Power Ignition Sensing Control Function, 12V/24V Selectable (43 x 36 mm)
URM01	Universal 19" Rack Mount Kit for Industrial Panel PC & Industrial Monitor
GST60A12-CIN1	Adapter AC/DC 12V 5A 60W, GST60A12-CIN1, wide temp(-30°C ~ +70°C)
GST120A24-CIN	Adapter AC/DC 24V 5A 120W, GST120A24-CIN, wide temp (-30°C ~ +70°C), level VI